



Specification S 3300EP – 2150 X34073

Clampingforce	3300kN
Openingstroke	720mm
Distance between tiebars	750x750mm
Mouldheight	200-720mm

Injection 2150	62mm 25 L/D screw
Shotvolume (max.)	951cm ³

Leaflet (separate file)

Options:

2x911c	hotrunner control unit 12 circuits, each 16A
2x924	quality monitoring on process
3x401	fixed platen steel
3x521	stop bolts for mechanical stop
3x526a	clampingforce control TLC-4
3x621	ejector, pressure adjustment on control cabinet
3x541f	air blow function, free programmable, V1 FP
3x542f	air blow function, free programmable, V2 FP
3x543f	air blow function, free programmable, V3 FP
3x544f	air blow function, free programmable, V4 FP
3x545f	air blow function, free programmable, V5 FP
3x546f	air blow function, free programmable, V6 FP
3x547g	air blow function, free programmable, V7 MP
3x548g	air blow function, free programmable, V8 MP
3x621	ejector, pressure adjustment on control cabinet
3x833c	interface robot with monitoring core(s) acc Euromap 67 / 12
3x847	ejector, monitoring in the mould
3x848	connection photocell
3x849b	photocell for drop-out protection
4x100a	Screw with 25 L/D ratio
4x380c	shut-off nozzle, sliding plug hydraulic
4x424a	screw with mixing head PE-2, armored
4x454	bi metallic cylinder
4x464	motor for screw drive with increased RPM (decreased torque)
4x466a	hopper with cover
4x480	cycle time shortening by special unit controls
4x921	cushion control
5x556	core puller NW10 double, 1xFP, 1x MP

- Connectorbox 5 outlets